

Shaft											Extract of DIN 7160				
Normal Size mm		Shaft Tolerance in 0.001 mm = .000039 inch													
	Above To	3 6	6 10	10 18	18 30	30 50	50 80	80 120	120 180	180 250	250 315				
Tolerance Zone		0 - 5	0 - 6	0 - 8	0 - 9	0 - 11	0 - 13	0 - 15	0 - 18	0 - 20	0 - 23				
h	5	0 - 5	0 - 6	0 - 8	0 - 9	0 - 11	0 - 13	0 - 15	0 - 18	0 - 20	0 - 23				
	6	0 - 8	0 - 9	0 - 11	0 - 13	0 - 16	0 - 19	0 - 22	0 - 25	0 - 29	0 - 32				
	js	+ 4 - 4	+ 4.5 - 4.5	+ 5.5 - 5.5	+ 6.5 - 6.5	+ 8 - 8	+ 9.5 - 9.5	+ 11 - 11	+ 12.5 - 12.5	+ 14.5 - 14.5	+ 16 - 16				
	7	+ 6 - 6	+ 7.5 - 7.5	+ 9 - 9	+ 10.5 - 10.5	+ 12.5 - 12.5	+ 15 - 15	+ 17.5 - 17.5	+ 20 - 20	+ 23 - 23	+ 26 - 26				
k	5	+ 6 + 1	+ 7 + 1	+ 9 + 1	+ 11 + 2	+ 13 + 2	+ 15 + 2	+ 18 + 3	+ 21 + 3	+ 24 + 4	+ 27 + 4				
	6	+ 9 + 1	+ 10 + 1	+ 12 + 1	+ 15 + 2	+ 18 + 2	+ 21 + 2	+ 25 + 3	+ 28 + 3	+ 33 + 4	+ 36 + 4				
	n	+ 16 + 8	+ 19 + 10	+ 23 + 12	+ 28 + 15	+ 33 + 17	+ 39 + 20	+ 45 + 23	+ 52 + 27	+ 60 + 31	+ 66 + 34				
	7	+ 20 + 8	+ 25 + 10	+ 30 + 12	+ 36 + 15	+ 42 + 17	+ 50 + 20	+ 58 + 23	+ 67 + 27	+ 77 + 31	+ 86 + 34				
Housing											Extract of DIN 7161				
Normal Size mm		Housing Tolerance in 0.001 mm = .000039 inch													
	Above To	3 6	6 10	10 18	18 30	30 50	50 80	80 120	120 180	180 250	250 315				
Tolerance Zone	H	+ 8 0	+ 9 0	+ 11 0	+ 13 0	+ 16 0	+ 19 0	+ 22 0	+ 25 0	+ 29 0	+ 32 0				
N	6	- 5 - 13	- 7 - 16	- 9 - 20	- 11 - 24	- 12 - 28	- 14 - 33	- 16 - 38	- 20 - 45	- 22 - 51	- 25 - 57				
	7	- 4 - 16	- 4 - 19	- 5 - 23	- 7 - 28	- 8 - 33	- 9 - 39	- 10 - 45	- 12 - 52	- 14 - 60	- 14 - 66				
Keyway and Key											Extract of DIN 6885 Bl. 1				
Normal Size mm		Keyway Tolerance in 0.001 mm = .000039 inch													
	Above To	8 10	10 12	12 17	17 22	22 30	30 38	38 44	44 50	50 58	58 65	65 75	75 85	85 95	95 110
Keysize (Width x Height)	3x3	4x4	5x5	6x6	8x7	10x8	12x8	14x9	16x10	18x11	20x12	22x14	25x14	28x16	32x18
Tolerance Zone P9 for keyway width	- 6 - 31	- 12 - 42			- 15 - 51			- 18 - 61			- 22 - 74			- 26 - 88	
Depth of Keyway (shaft)	1.8	2.5	3	3.5	4	5	5	5.5	6	7	7.5	9	9	10	11
Tolerance	+ 100				+ 200										
Depth of Keyway (hub)	1.4	1.8	2.3	2.8	3.3	3.3	3.3	3.8	4.3	4.4	4.9	5.4	5.4	6.4	7.4
Tolerance	+ 100				+ 200										
Keyway and Key											Extract of DIN 6885 Bl. 3				
Normal Size mm		Keyway Tolerance in 0.001 mm = .000039 inch													
	Above To	8 10	10 12	12 17	17 22	22 30	30 38	38 44	44 50	50 58	58 65	65 75	75 85	85 95	95 110
Keysize (Width x Height)					5x3	6x4	8x5	10x6	12x6	14x6	16x7	18x7	20x8	22x9	25x9
Tolerance Zone P9 for keyway width					- 12 - 42		- 15 - 51		- 18 - 61			- 22 - 74		- 26 - 88	
Depth of Keyway (shaft)					1.9	2.5	3.1	3.7	3.9	4	4.7	4.8	5.4	6	6.2
Tolerance					+ 100					+ 200					7.6
Depth of Keyway (hub)					1.2	1.6	2	2.4	2.2	2.1	2.4	2.3	2.7	3.1	2.9
Tolerance					+ 100		+ 100		+ 100		+ 100		+ 100		+ 100